

Resin Number: 29316

Last Updated: 9/30/2005

Material Number:

Page 1 of 1

DESCRIPTION

Varcum 29316 is a two-step, powder phenolic resin.

APPLICATION

- Medium-hard, dense-grades of cold pressed-snagging wheels.
- Coarse-grain, high-density cutoff wheels.

FEATURES

Minimizes the amount of wetting agent required.

TYPICAL PROPERTIES

		<u>Test Method</u>
Screen % on 200 Mesh	3.00	DCT 4007A
Inclined Plate Flow @ 125°C, mm	39.00	DCT 4009A
Hexa, %	9.05	DCT 4019A

Durez test methods are available upon request.

SOLUBILITY

Soluble in alcohols, ketones and esters although solutions have slight haze or sediment. Not soluble in aromatic hydrocarbons, but solutions in true solvents will tolerate the addition of aromatic hydrocarbons.

STORAGE

This product is a stable material that has little or no tendency to lump when maintained in closed containers. Store in a cool dry location at 75°F or less.

PACKAGING AND SHIPPING

Available in non-returnable fiber drums, 250 pounds net, and 50 pound bags. This product is not DOT regulated in drums and bags.

READ THE MATERIAL SAFETY DATA SHEET BEFORE HANDLING,
STORING OR USING THIS PRODUCT.