

Resin Number: 34071

Last Updated: 10/11/2007

Material Number:

Page 1 of 1

DESCRIPTION

Durez 34071 is a butyl etherified phenol-formaldehyde crosslinker resin in butanol solvent.

APPLICATION

Durez 34071 is recommended for use in metal coating applications such as:

- Coatings for food packaging
- Drum linings
- Spray applied metal primers and topcoats

FEATURES

- Excellent chemical resistance
- Very good adhesion
- Very good flexibility
- Low temperature cure response
- High solids content for low VOC application

TYPICAL PROPERTIES

		<u>Test Method</u>
Non Volatile, %	76.00	DCT 4005A
Viscosity @ 25°C, cps	2,200.00	DCT 4003F
Specific Gravity	1.10	DCT 5075
pH	5.50	DCT 4064A
Xylene Tolerance, %	400 min	DCT 4012

Durez test methods are available upon request.

STORAGE

This product is a heat reactive material and should be stored in closed containers at, or below 40°F.

PACKAGING AND SHIPPING

Available in 55 gallon drums, 550 pounds net. Check with your local salesperson for packaging options and availability.

READ THE MATERIAL SAFETY DATA SHEET BEFORE HANDLING,
STORING OR USING THIS PRODUCT.