

Resin Number: 92600

Last Updated: 3/12/2001

Material Number:

Page 1 of 1

DESCRIPTION

Varcum 92600 is a liquid one-step phenolic resin in ethanol.

APPLICATION

Varcum 92600 is an unmodified phenolic resin solution producing baked films that are outstanding in resistance to almost all acids, salt and fresh water, solvents, oils and other organic chemicals. They have good durability and abrasion resistance. Varcum 92600 is a fast curing resin solution, and the relatively low temperature and short time necessary for its polymerization result in light colored films. Baked films of Varcum 92600 can be plasticized sufficiently to enable them to withstand shocks or rough handling.

TYPICAL PROPERTIES

		<u>Test Method</u>
Viscosity @ 25°C, cps	805.00	DCT 4003F
Non Volatile, %	55.00	DCT 4005A
pH	4.50	DCT 4064A
Color	3.50	DCT 4075A

Durez test methods are available upon request.

STORAGE

This product is a heat reactive material and should be stored in closed containers at, or below 40°F.

PACKAGING AND SHIPPING

Available in 55 gallon steel drums, 400 pounds net. This product is DOT regulated and shipped as a FLAMMABLE LIQUID, UN1866.

READ THE MATERIAL SAFETY DATA SHEET BEFORE HANDLING,
STORING OR USING THIS PRODUCT.